### **Beacon Gateway**

#### **FSC-BP201** Datasheet



### 1. Description

FSC-BP201 is an integrated Bluetooth and Wi-Fi gateway, which can be paired with the Internet of Things platform FeasyCloud and other 3<sup>rd</sup> party platform, BEACON positioning tags and temperature and humidity sensor tags. It can help realize the complete warehouse solution of asset positioning, asset protection, alarm management and energy efficiency management.

With the iOS & Android FeasyMonitor SDK, the developers can take advantage of the flexibility of the SDK and focus on their own application. Meanwhile, FeasyMonitor SDK compiled app is available to download from both the iOS and Android platforms (search 'FeasyMonitor' to download).



#### 2. Features

- Bluetooth 5.0 Compliant
- Wi-Fi 2.4G & 5G Dual Bands
- Wi-Fi network configuration: Through the Web
- Powered by USB
- Built-in 260 mAh lithium battery
- Minutely/daily/weekly/monthly/yearly charts for data displaying
- Manage over mobile app and web management console
- Customizable Color, Logo, Hardware, Software




# 3. Application Scenarios

- Hospital
- Warehouse
- Shopping Mall
- Airport
- School
- Logistics



## 4. Application Diagram





### 5. Parameters


Item	Description	
Supported Beacon	FeasyBeacon & Standard beacon( iBeacon, Eddystone, Altbeacon)	
Network Configuration	Through the Web	
Data Display	Minute, Day, Week, Month, Year	
Offline Monitoring	Point-to-point monitoring by FeasyMonitor app	
Management Method	FeasyMonitor app, web management console	
Mobile SDK & App Compatibility	iOS 7.0+, Android 4.3+	
Firmware Upgrading	OTA (upgrade firmware over the air)	


# **6. Product Specifications**

Item	Description	
Bluetooth Version	Bluetooth 5.0	
Wi-Fi Standard	802.11 a/b/g/n (2.4G + 5G)	
TX power	8 dBm (Bluetooth), 17.5 dBm (Wi-Fi)	
Antenna	PCB antenna	
Power Supply	Micro USB, 260mAh lithium battery	
Battery Life	2 hours	
Material	ABS plastic	
Color	White, or customized	
Size	Diameter 69 mm, height 10 mm	
Net weight	30.3 g	
Protection	IP40	
Operating temperature	-20°C to +60°C	



### 7. Dimensions





#### 8. Declaration

The contents of this datasheet are subject to change without prior notice for further improvement. Feasycom team reserves all the rights for the final explanation.

Please contact Feasycom sales team or visit <a href="https://www.feasycom.com/">https://www.feasycom.com/</a> to get more related information if needed.

### 9. Contact Information

Shenzhen Feasycom Co.,LTD

Address: Rm 508, Building A, Fenghuang Zhigu, No.50, Tiezai Road, Xixiang, Baoan

District, Shenzhen, 518102, China

Telephone: 86-755-23062695



Support: <a href="mailto:support@feasycom.com">support@feasycom.com</a>

Sales Service: <a href="mailto:sales@feasycom.com">sales@feasycom.com</a>

# **Revision History**

Version	Changes	Author
1.0	Initial Release	Jerry
1.1	Update description	Origami